



## The Agatec CPL50 is a cross line laser with built-in 180° plumb beam, ideal for floor-to-ceiling point transfer.

It also has horizontal and vertical fan angles, cross line, and locked line angle in manual mode which allows you to match an angle between any two points. It features pulse mode for outdoor detector use (optional). Delivered with drywall adaptor, especially designed for stude installation, and swivel mount, for inclined levels.

- High visibility cross line, with plumb up and down
- Full package, with swivel and magnetic multi use mount
- It works also outdoor. with laser receiver (optional)




**INCLUDES** Laser, multi use mount, swivel mount, pouch, 3 x AA batteries

## **RECOMMENDED ACCESSORIES** LS30. Laser receiver that enables

reception in very bright light conditions, or at long distance.



Pole mount. For floor to ceiling applications.









SPECIFICATIONS	Art. No. 775208
Range	30 m indoor
	50 m outdoor with detector LS30
Accuracy	± 3 mm at 10 m
Self-leveling range	± 5°
Cross line	130° horizontal &
	140° vertical fan angles
Plumb	Floor to ceiling
Power	3 x AA batteries
Battery life	25 hrs. 1-beam operation;
	12 hrs. with 2 beams
IP	IP54
Weight w/o batteries, mount	470 g
Size	110 x 57 x 97 mm
Warranty	2 years




The Agatec CL30 is a self-leveling laser with a highly visible 90° cross line for all interior applications.

It has four line options: horizontal fan angle, vertical fan angle, cross line, and locked line angle in manual mode which allows you to match an angle between any two points.

Applications: installing ceilings,

Applications: installing ceilings, walls, walls tile, hanging cabinets, shelving, electrical boxes.

- High lines visibility
- Very easy to operate, one button tool
- For any professional indoor applications



Ideal for alignment works, as tiles and cabinet installation





**INCLUDES**Laser, pouch, 3 x AA batteries



www.agatec.com

SPECIFICATIONS	Art. No. 775207
Range	30 m
Accuracy	± 3 mm at 10 m
Self-leveling range	± 4°
Cross line	130° H & V fan angles
Power	3 x AA batteries
Battery life	25 hrs. 1-beam operation;
	12 hrs. with 2 beams
<u>IP</u>	IP54
Weight w/o batteries, mount	310 g
Size	84 x 62 x 90 mm
Warranty	2 years